



2019 Super Late Model Specifications & Guidelines

IMPORTANT: Competitors MUST READ the "Additional Rules" Section at the end for additional rules specific to a Track or Series.

A. Eligible Cars and Bodies Guidelines **THE NEW FIVE STAR GEN-6 BODY IS NOT ALLOWED NOR HAS BEEN APPROVED FOR 2019.**

- All competing cars will be full-sized, stock American manufactured passenger car bodies. 2018 A-B-C Body Rules apply unless otherwise specified herein. Refer to A-B-C Rulebook and guidelines for details. Also, no panels allowed extending top edge of doors. No under car panning outside of frame rails and no further than drivers' box front or rear of bottom of driver's seat. No under car panning outside of frame rails and no further than drivers' tub front or rear at the bottom of the frame.
- Maximum drivers tub length is 52 ½" and the maximum width of frame is 53 ½". Any holes in body not being used must be covered and remain so during the race.
- A-Pillar vent windows may only have 1 inch of straight-line deflection. The surface must be smooth and must not have bead rolls or breaks. Front nose valance may only be a single layer and may only be a maximum 3/16" thick and may be only a maximum of 3.
- Rub rail are discouraged and may only be used if they are polycarbonate.
- If exhaust exits through the door, installation must include an exhaust flange that is mounted flush to the door. Maximum ½" gap around the exhaust pipe. Pipe must not protrude through door.
- At all times, the ABC "A" measurement must maintain a min. length of 11.5 inches. Also, 20 inches is the min. length allowed for the nose, measured from the bottom, leading edge at center, up to the hood seam. **In 2020 the Minimum/ Maximum Nose Height will be: Minimum nose, body and frame height is 4" and Maximum of 7".**
- The air box between the nose and radiator may have no pieces wider than the radiator. The standard opening for the grill screen area, as approved for manufacturer's production, must be maintained at all times. Only ABC manufacturer's standard mesh screen may be used for the radiator opening in the nose. No cool down units, pumps, exotic fans allowed. If you have to ask it's not legal.
- No types of under-body air deflectors are allowed. All air for blowers or coolers in the engine compartment must be pulled from the nose or the radiator air box. Air may not be blown or forced onto the tire or bead. Air may only be directed to the brake rotors. The duct work between the nose and the radiator may be no wider than 29" and may not be carbon fiber.
- Tape may not be used anywhere on the car to control the flow of air or seal/secure seams between body panels (unless approved for repairs). Only exception is that tape MAY be used on the radiator grill opening **and brake ducts in the nose.**
- Titanium, **Inconel** or exotic metal are not allowed for use in any way on the race car.
- 66-inch maximum tread width for all cars.
- Interiors must be steel or aluminum only.
- No Data Acquisition equipment/wiring is allowed in the car on officially recognized race or practice days.
- All Transponders must be mounted 160" inches (front of nose to the center of transponder) from front of the nose and on outside of right-side frame rail.**
- All cars must go through technical inspection prior to car taking to the track for practice. Cars will be weighed with driver, and may be done prior to or after qualifying and prior to or after the feature. Reading of designated scales will be official. Issues discovered in pre-practice tech that are not fixed to satisfaction by pre-qualifying tech will result in the loss of 1 qualifying lap.
- Minimum Base Weight: **2800 lbs.** (see "Series/Track Additional Rules" section for additional weight breaks or penalties). 58.0% Max. Left side weight at all times (without refueling). For post-race total weight rules, *if requested by officials, teams may be required to refuel*, or officials may utilize "1 lb. per lap" burn-off.

B. Engines

Basic Engine Guidelines

- Use of any engine under 347 Cubic Inches will require a 50lb penalty.
- Engines with rear mounted distributors will be located so the forward most spark plug is no more than two inches (2") from the center line of the upper ball joints. Engines with front mounted distributors: up to four inches (4") setback from centerline of upper ball joints. Crate Engines may use four-inch (4") setback.
- Engines may not be offset more than one inch (1") from centerline of car.
- Front center of crankshaft must have at least ten inches (10") of ground clearance. Crate Engines must be at least 11 inches.
- Standard steel blocks only. No Carbon Compacted blocks of any type.
- No Ford D3, SC, or other High Port heads. The following are the ONLY approved Ford heads: A, B, C, C3, and C35. These heads must remain unaltered other than porting and polishing. No altering will be allowed so as to change runner floor or roof height to raise port or ports, these heads will be considered high ports and are not permitted. Runner floor and runner roof heights must remain as manufactured from Ford.
- No Overhead Camshafts.
- A maximum 16-inch (O.D.) air element and housing must be used.
- Carburetor restriction must be done with a solid plate or cone type system only, and may NOT be externally adjustable in any way. No adjustments may be made to the

carb/restrictor package following qualifying. Teams will race with the same package they qualify with.

- Any competitor that finishes in the top 5 may be required, at their expense, to remove the intake, heads, and/or oil pan for inspection purposes.
- Externally lightened blocks will receive a 25-50 lb total weight penalty.
- All oil pumps must be mounted to front of engine.

9:1 Compression Engine 362 Max Cubic Inches/Cast Iron Block/

(This package may be phased out in the near future)

- Cannot exceed 9.5:1 compression. Method of determining compression will be at the discretion of Officials. 8200 rpm max.
- Minimum valve angle: GM-18 degrees; Ford 9 degrees with 4 degrees valve center; and Mopar 12 degrees. (+/- 2 degrees)
- Steel or aluminum cylinder heads.
- Steel standard production crankshaft; balancing, lightening, stroking allowed.
- Any camshaft, any steel lifter, any rockers arms. Gear drives allowed.
- Steel or aluminum intake. No fabricated intakes. No material may be added to production intake manifold to increase carb height. No welded-on spacers or air deflection devices allowed in intake. No part of carb spacer shall enter the intake.
- 390 CFM 4bbl Part #6895 or #80507. Carburetors must pass inspection at any time regardless of temperature. Booster bar may be removed from center of booster (max inside dia. of booster .473) and the booster may be tapered from the center seam down (booster must retain .700 length minimum) but all 4 boosters must be the same style. No other modifications are allowed on carbs.
- 1" Maximum spacer allowed but cannot extend into manifold.

Southern Super Parts Engine (SSPE)

Southern Super Parts Engine (May Be Claimed for \$21,000 + pulling fee)

- Maximum Engine displacement is 362 cubic inches.
- Maximum compression ratio is 11.5:1 with +.5 tolerance.
- Any flat top piston permitted with 927 wrist pin and .043 x .043x 3mm ring package only. Pistons must not extend out of the top of engine block. Maximum racer cost of \$1400.00 per set.
- Cast Iron engine blocks only.
- Intake must remain stock. Absolutely no match porting or blasting of any kind permitted. Slotting of bolt holes, water lines and matching of sides allowed. Ford part #: Edelbrock 2928, 2929, or 2934 only. Chevy part#: Edelbrock 2814 or 2892 only.
- Crankshaft must have a minimum weight of 40 pounds (with front timing pulley or sprocket). Minimum main size Chevy 2.300/ Ford 2.250. Maximum advertised racer cost of \$1400.00
- Connecting rods: Minimum rod journal size 1.850". Absolutely no piston-guided rods permitted. Maximum racer cost of \$1400.00 per set. No titanium rods permitted. Minimum rod weight 560 grams.
- Listed Brodix Cylinder Heads only. Heads may be surfaced to achieve proper compression ratio. Absolutely no other work of any kind will be permitted to the intake ports, exhaust ports, or combustion chambers. Ford part #: SP STS T-1 F STD 225-SSPE. Must retain minimum valve angle of 20°. Chevy Part #: SP STS T-1 STD 227-SSPE. Must retain min. valve angle of 21°. Multi-angle valve job permitted. Absolutely no blending of valve job below valve seat permitted. Chamber must retain shape 3/8" above valve seat. Minimal blending due to multi-valve jobs permitted.
- Maximum valve size: Intake 2.08", Exhaust 1.60", Stem size 11/32". Intake valve may be titanium or stainless steel. Exhaust must be stainless steel.
- No Titanium valve springs permitted. Maximum racer cost: \$425.00 per set. Titanium retainers permitted. Lock angles not specified.
- Camshaft must be Competition Cam Part #: 21151712. Camshaft must be installed on 104" intake centerline +/- 1". Roller lifters, maximum racer cost of \$700.00 per set. Maximum lift of .715" while using 1.6 rockers checked at valve with zero lash. Maximum 1.6 rocker arm racer cost of \$1,500.00 per set. Magnetic-type push rods only. No keyway guided lifters permitted.
- Maximum 5 stage dry sump oil pump permitted. Maximum racer cost of \$1,250.00.
- Oil pan must have 1" inspection hole. Absolutely no sectional pans permitted. Open box pans only (NO windage tray / scrapers etc.). Maximum racer cost of \$550.00.
- Ignition System may only be FAST Ignition part # 6000-6701. Mount on right side of car dials point out the passenger side. The mag positive & negative shall be a maximum length of 62 inches. Must be remain uncut or spliced and on top of dash in clear view. Mandatory 8000 RPM Rev Limiter must be installed and fully functional. Absolutely no crank trigger pickups permitted.
- Carburetor must be an unaltered 750 CFM 4779, 80528 Holley permitted. Carburetor must pass inspection at any time regardless of temperature. Maximum 1" carburetor spacer permitted on Ford motor only. Maximum ½" carburetor spacer permitted on Chevrolet motor only. *No Internally lightened blocks.*

"Other Engines"

1. S.E.A.L. approved McGunegill, Hammer, Ford 374D and Florida SPEC "Sealed Engines" may also be used. The 6 existing Ford 374D engines are grandfathered for another year. That package will be eliminated in the near future. No new Ford 374D engines may be built. If necessary, series officials may add or subtract weight to ensure fair competition. Any tampering of seals or established construction of these engines is grounds for immediate disqualification. Additional tech rules will apply. The maximum RPM is the series mandated 7600 for these engines. Rev limiting device must be operational at all times with RPM Dials securely covered. All Sealed engines must use the gauge legal, 750 carb as described in the SSPE section. NO Internally lightened blocks.
2. The "ACE" Engine as commonly used in the ARCA Midwest Tour may also be used with a 750 carb as described in SSPE engine section. Series officials may add or subtract weight to ensure fair competition. 7800 rpm max.
3. Crate engines may also be used. Series officials may add or subtract weight to ensure fair competition. Cars utilizing crate engines must use the engine, carb and ignition specifications from the FFS Pro rules.

C. Fuel System

1. **Sunoco Purple 110 is the Spec fuel of the Southern Super Series.** Fuel samples may be taken at any time and tested. Alcohol, nitro-methane, nitrous oxide, other oxygenating agents, other additives and/or fuels that contain masking agents or oxygen are not permitted. Street-use pump gas is not allowed. Use of such substances or additives will result in immediate disqualification.
2. No electric fuel pumps or forced induction of any kind are permitted.
3. No icing or cooling of fuel system.
4. A fuel cell will be mandatory with a 22-gallon (U.S.) maximum. Fuel cell must have a minimum of eight inches (8") ground clearance. Fuel cell must be equipped with at least two (2) protective straps completely around the cell. Fuel cell must be mounted securely behind the rear axle of the car. Cars must have a minimum 1/8" steel plate, or similar strength aluminum plate, between fuel cell and rear end. A similar plate at the rear of the fuel cell is recommended. All cars must have safety bar at the rear of the fuel cell. At a minimum, all fuel cell configurations must include a rubber type cell in a steel container. No "U" Shaped Fuel Cells or non-standard-shaped fuel cells.

D. Ignition

1. Battery powered ignition. Vehicle MUST start under own power.
2. Max. 16 Volt Battery. Car must be able to start with a 12-volt battery. No Mags.
3. All wiring must be sealed. No unplugged wiring. All ignition boxes must be mounted on the passenger side, in plain view, and out of reach of the driver...and...all wires to the distributor must be run separately and not part of a bigger loom or wiring harness.
4. All teams must only use ONE FAST Ignition part# 6000-6700 (HI-6RC) and a Coil part# 730-0192 (PS92N), mounted on a tray from FAST.

E. Suspension

1. No fifth (5th) coil, torque arm or lift bar suspensions will be permitted. No birdcage set-ups of any kind (3 or 4 link). Trailing arms must mount to rear end in a solid fashion (heim allowed) and no part of the trailing arm mounting may freely rotate around the rear end. All parts of rear suspension must be solid, one-piece construction with no moving parts, with one heim at each end. All mounts for trailing arms, third links and track bars must also be solid and may not have the ability to move.
2. The wheelbase difference from left to right may not exceed 1/2 inch.
3. **No driver adjustments other than ONE adjuster for brakes.**
4. Coil Springs and Spindles must be Steel. (Exception: approved Coleman Spindle)
5. **NO Traction Control Devices of any kind - If any 'traction control' device is found, the driver and owner will be disqualified from the event, the car will be confiscated until a \$15,000 fine is paid. Additionally, the driver and owner will receive a lifetime ban from all events.**
6. One shock per wheel. Shocks must be only mechanical in nature and no part of suspension or shocks may utilize electricity.

F. Wheels and Tires

1. Steel 10" wheels and lug nuts only with car number decal. **Unless otherwise specified on the entry form, the spec tire will be Series Designated Hoosier F45.**
2. **Bleeders are not allowed. Hidden bleeders will be checked for!!!**
3. Cars must start the feature on the same tires on which they qualified. Cars running the last chance race may change tires prior to that race, but must return to the qualifying tire for the feature. Cars that run the last chance race on qualifying tires will be allowed to change tires prior to the feature.
4. Use of tire softening or altering agents will not be permitted. Use of such substances will result in immediate disqualification, loss of points and money.

G. Transmission, Driveshaft, Rear End

1. Full standard type transmission only will be permitted. No quick-change transmissions will be permitted. Automatic transmissions will not be permitted. Crate engine teams may use their transmission rules with no weight penalty.
2. A minimum of one reverse and two forward gears will be required.
3. Multi-disc clutches will be permitted. No direct drives. Conventional clutch mounted to fly wheel only will be permitted. Any transmission that does not meet these guidelines may be assessed a minimum 25 lbs penalty.
4. No carbon fiber or nonstandard material clutches. **The minimum clutch diameter is 5.5".** No "slipper" or "centrifugal" clutches allowed.
5. Driveshaft must be equipped with a minimum of two (2) safety straps and must be painted white. Drive shafts must be made of Aluminum or Steel only, and use no other materials (i.e. carbon fiber, etc).

H. Brakes

1. Vehicle must be equipped with four-wheel hydraulic brakes.
2. No carbon fiber rotors. **Only steel rotors are allowed (no titanium).**
3. Brake fluid circulators permitted. Liquid or gas cooling not permitted.

I. Safety

1. Radio communication to the drivers is mandatory, with a minimum of one (1) spotter for each team. **Spotter must have the capability to monitor series race control with a scanner or stand-alone radio.**
2. Approved seat belts and double shoulder harness will be required, no older than five (5) years. A crotch strap will be required.
3. A capable form of head & neck restraint must be used. A strap-type neck restraint is mandatory (No Neck Collars). Drivers will not be allowed on the racetrack at any time without proper neck restraints in place.
4. Helmet must be 2010 Snell standard or better and have sticker visible for inspection. Full-face helmets required.
5. Clean, full driving suit and approved gloves for fire protection are mandatory.
6. Side plate for driver's door will be mandatory. Must be 12 inches (12") high post-to-post, 1/16" minimum thickness steel or and must be fastened with a minimum of six (6) half-inch bolts or securely welded to series' approval.
7. Driver's window must be equipped with safety net with quick release-latch. String window nets will not be permitted. The minimum net size must be 22" wide and 16" high. When latched, the window net must fit and pull tight.
8. Resilient padding designed for roll bar use must be installed on any roll cage member which can be reached by any extremity of the driver while driver is normally seated with restraints fastened. Steering wheel must be padded.
9. All lead weights must be painted white, with the car number painted on each individual piece. All lead weights must be securely fastened. Any lost weight will result in a \$10 per pound fine. **No Tungsten or similar weight allowed!** Added weight must not be used as panning or aero advantage.
10. All competing teams must possess a minimum 10 lb. Aluminum working fire extinguisher while in attendance in pits, and this item must be presented at inspection. Car number must be painted on fire extinguisher
11. A main electrical cut-off switch needs to be clearly marked and easily accessible to safety crews.
12. Numbers must be a minimum of 21" in height, with body of each character a minimum of 3" in width and must be professionally placed on each door. A number will be required on top, readable from the infield.
13. A car number at least six inches (6") in height must be placed in the upper right-hand corner of the windshield.
14. Roll cage must be constructed of 1 3/4" OD round steel tubing with a minimum wall thickness of .090". Three inches (3") maximum gussets measured diagonally must be welded in main roll cage area where a 90-degree angle exists or where the roll cage meets the main frame rails. The main frame rails / bolt-on clips must be steel from radiator area to behind the fuel cell. Main Frame rails must be a minimum of 2" x 3" rectangular steel. Bumper bars and right-side door bars must be a minimum of .065 x 1 1/4 inch tubing.
15. No part of any cooling system may be located in driver's compartment.
16. Batteries must be securely mounted outside of driver's compartment.
17. A working Fire Suppression system or driver accessible fire extinguisher is required. **All cars must have an OBERG or SRI fuel shut off at the point the fuel exits the cell.**

I. Economy Package

1. **Cars utilizing a working locked rear end (i.e. a spool or similar) may deduct 50 lbs. off their total weight and 58.5% left side. Spools mandatory in 2020. (Excluding Bristol).**

J. OFFICIAL DECISIONS

1. Any situation not specifically covered in these rules will be acted upon by the official or officials in charge at the time, whose decision will be final and binding.
2. Any disagreement over technical questions or operations will be resolved by series officials. When decision is rendered, decision is final and binding
3. Continuous developments in racing may necessitate changes which cannot be anticipated at the time rules are formulated. If necessary, rules may be updated, changed, deleted or added to at the discretion of the officials.
4. At certain events, to encourage participation of local competitors, the officials may alter the rules for those cars to try and create a level playing field for cars that might fall outside of the normal rules. Official's decisions are final.

Additional SSS Rules Section

1. Weight deduction for Crate Engines, per track, if any, will be announced on the event's entry form.
2. **Mandatory a muffler must be used at Montgomery and Nashville** and installed in a configuration that will suppress exhaust noise to a maximum of 99db's at 100 feet. Any car that is consistently tested above 99db's will receive additional penalties up to and including disqualification.
3. All one-day shows will be Impound races.
4. Mandatory minimum fuel purchase at each event.
5. No cell phones allowed in car at anytime.